

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-107318

(43)Date of publication of application : 19.04.1990

(51)Int.Cl.

B01D 63/02

(21)Application number : 63-259184

(71)Applicant : DAICEL CHEM IND LTD

(22)Date of filing : 14.10.1988


(72)Inventor : KUMAMI KAZUHISA
MATSUMOTO YOSHIMASA

(54) MEMBRANE MODULE OF HOLLOW FIBER TYPE

(57)Abstract:

PURPOSE: To prevent leakages through the boundary surfaces of hollow fibers and their epoxy resin sealing layer by providing a protection layer on the outer periphery of the hollow fiber to cover the aforesaid boundary surfaces in such manner that a part thereof is raised to a specific height along the outer periphery of the adjoining hollow fiber.

CONSTITUTION: Hollow fibers 4 are provided which are adhesively sealed at their ends by epoxy resin 2. A protection layer 3 consisting of polyurethane resin and having an elongation rate of not less than 10% is provided on the outer periphery of the hollow fiber 4 in such manner that the projection layer covers the boundary surfaces of the epoxy resin and the hollow fiber with a part 5 thereof raised to a height of not less than 1mm along the outer periphery of the adjoining hollow fiber 4. As a result, the boundary surfaces of the hollow fiber and the epoxy sealing layer are reinforced, thereby permitting a reduction in the occurrence of the leakages due to an external force.



LEGAL STATUS

[Date of request for examination]